

## Lieferprogramm / Range of Delivery

### T-Stücke DIN 2615-1 / Tees DIN 2615-1

Abmessungen / Dimensions				Material / Material Grade		Abmessungen / Dimensions				Material / Material Grade				
d1	s1	d2	s2	St 37.0/ S235	St 35.8// P235GH	d1	s1	d2	s2	St 37.0/ S235	St 35.8// P235GH			
Außen Ø / Outside Ø	Wanddicke / Wallthickness	Außen Ø / Outside Ø	Wanddicke / Wallthickness			Außen Ø / Outside Ø	Wanddicke / Wallthickness	Außen Ø / Outside Ø	Wanddicke / Wallthickness					
mm	mm	mm	mm			mm	mm	mm	mm					
17,2	1,8	17,2	1,8		✓	38,0	2,6	38,0	2,6		✓			
	2,9	17,2	2,9		✓									
	3,2	17,2	3,2		✓									
21,3	2,0	21,3	2,0		✓	42,4	2,6	42,4	2,6	✓	✓			
		17,2	1,8		✓			33,7	2,6	✓				
		26,9	2,3		✓			26,9	2,3	✓				
	3,2	21,3	3,2		✓			21,3	2,0	✓				
	4,0	17,2	2,9		✓			42,4	3,6	✓				
		17,2	3,2		✓			33,7	3,2	✓				
26,9	2,3	26,9	2,3		✓	44,5	2,6	44,5	2,6		✓			
		21,3	2,0		✓			33,7	4,0	✓				
		17,2	1,8		✓			26,9	4,0	✓				
	3,2	26,9	3,2		✓			21,3	4,0	✓				
	4,0	21,3	3,2		✓			48,3	2,6	48,3	2,6		✓	
		17,2	2,9		✓			42,4	2,6	42,4	2,6	✓	✓	
17,2		3,2		✓	33,7	2,6	33,7	2,6	✓	✓				
30,0	2,6	30,0	2,6		✓	48,3	2,6	48,3	2,6	✓	✓			
		26,9	4,0		✓			26,9	2,3	✓				
		21,3	4,0		✓			21,3	2,0	✓				
33,7	2,6	33,7	2,6	✓	✓	57,0	2,9	57,0	2,9		✓			
		26,9	2,3		✓			3,6	26,9	2,9	✓			
		21,3	2,0		✓			4,0	48,3	4,0	✓			
		17,2	1,8		✓			4,0	48,3	4,0	✓			
		3,2	33,7	3,2				✓	42,4	3,6	✓			
			26,9	3,2				✓	33,7	3,2	✓			
	3,6	21,3	3,2		✓			26,9	3,2	✓				
		17,2	2,9		✓			21,3	3,2	✓				
		33,7	3,6		✓			4,5	48,3	4,5	✓			
	4,0	3,6	33,7	4,0				✓	57,0	2,9	57,0	2,9		✓
			26,9	4,0				✓			5,0	48,3	5,0	✓
			21,3	4,0				✓			42,4	4,0	✓	
17,2		3,2		✓	33,7	4,0	✓							
4,0		33,7	4,0		✓	26,9	4,0	✓						
		26,9	4,0		✓	21,3	4,0	✓						
4,0	21,3	4,0		✓	6,3	48,3	6,3	✓						
	17,2	3,2		✓										

Sortimentsangaben unter Vorbehalt/Assortment subject to change

Lieferprogramm / Range of Delivery

T-Stücke DIN 2615-1 / Tees DIN 2615-1

Abmessungen / Dimensions				Material / Material Grade		Abmessungen / Dimensions				Material / Material Grade		
d1	s1	d2	s2	St 37.0/ S235	St 35.8// P235GH	d1	s1	d2	s2	St 37.0/ S235	St 35.8// P235GH	
Außen Ø / Outside Ø	Wanddicke / Wallthickness	Außen Ø / Outside Ø	Wanddicke / Wallthickness			Außen Ø / Outside Ø	Wanddicke / Wallthickness	Außen Ø / Outside Ø	Wanddicke / Wallthickness			
mm	mm	mm	mm			mm	mm	mm	mm			
60,3	2,9	60,3	2,9	✓	✓	76,1	5,6	76,1	5,6		✓	
		48,3	2,6		✓			6,3	76,1	6,3		✓
		42,4	2,6		✓			7,1	60,3	6,3		✓
		33,7	2,6		✓				76,1	7,1		✓
		26,9	2,3		✓		60,3		5,6		✓	
		21,3	2,0		✓		48,3		5,0		✓	
		4,0	60,3	4,0			✓	42,4	4,0		✓	
	4,5		60,3	4,5			✓	33,7	4,0		✓	
			48,3	4,0			✓	88,9	3,2	88,9	3,2	
		48,3	4,5		✓		76,1			2,9		✓
	42,4	3,6		✓	60,3		2,9				✓	
	33,7	3,2		✓	48,3		2,6				✓	
	26,9	3,2		✓	42,4		2,6				✓	
	21,3	3,2		✓	33,7		2,6			✓		
	5,6	60,3	5,6		✓		4,5		88,9	4,5		✓
		48,3	4,0		✓				76,1	4,5		✓
		48,3	5,0		✓				60,3	4,5		✓
		42,4	4,0		✓				48,3	4,5		✓
		33,7	4,0		✓			5,6	88,9	5,6		✓
	26,9	4,0		✓	76,1		5,0			✓		
21,3	4,0		✓	60,3	4,5		✓					
6,3	60,3	6,3		✓	48,3	3,6			✓			
	2,9	76,1	2,9	✓	✓	48,3	4,0			✓		
		60,3	2,9		✓	42,4	3,6		✓			
48,3		2,6		✓	33,7	3,2		✓				
42,4		2,6		✓	6,3	88,9	6,3		✓			
33,7		2,6		✓		76,1	6,3		✓			
4,0		60,3	4,0		✓	8,0	88,9	8,0		✓		
		4,5	76,1	4,5			✓	76,1	7,1		✓	
60,3			4,5		✓		60,3	5,6		✓		
48,3			4,5		✓		48,3	5,0		✓		
5,0		76,1	5,0		✓		42,4	4,0		✓		
	60,3	4,5		✓	33,7	4,0		✓				
	48,3	4,0		✓	108,0	3,6	108,0	3,6		✓		
	42,4	3,6		✓			88,9	3,2		✓		
33,7	3,2		✓									

Sortimentsangaben unter Vorbehalt/Assortment subject to change

## Lieferprogramm / Range of Delivery

### T-Stücke DIN 2615-1 / Tees DIN 2615-1

Abmessungen / Dimensions				Material / Material Grade		Abmessungen / Dimensions				Material / Material Grade		
d1	s1	d2	s2	St 37.0/ S235	St 35.8// P235GH	d1	s1	d2	s2	St 37.0/ S235	St 35.8// P235GH	
Außen Ø / Outside Ø	Wanddicke / Wallthickness	Außen Ø / Outside Ø	Wanddicke / Wallthickness			Außen Ø / Outside Ø	Wanddicke / Wallthickness	Außen Ø / Outside Ø	Wanddicke / Wallthickness			
mm	mm	mm	mm			mm	mm	mm	mm			
108,0	3,6	76,1	2,9		✓	139,7	4,0	88,9	3,2		✓	
		60,0	2,9		✓			76,1	2,9		✓	
		48,3	2,6		✓			60,3	2,9		✓	
114,3	3,6	114,3	3,6	✓	✓	4,5	139,7	114,3	4,5		✓	
		88,9	3,2		✓			114,3	4,5		✓	
		76,1	2,9		✓			108,0	3,6		✓	
		60,3	2,9		✓			88,9	4,5		✓	
		48,3	2,6		✓			76,1	4,5		✓	
	4,5	114,3	42,4	2,6		✓	6,3	139,7	114,3	6,3		✓
			88,9	4,5		✓			114,3	6,3		✓
			88,9	4,5		✓			88,9	5,6		✓
			76,1	4,5		✓			88,9	6,3		✓
			60,3	4,0		✓			76,1	5,0		✓
	6,3	114,3	60,3	4,5		✓	10,0	139,7	76,1	6,3		✓
			60,3	4,5		✓			60,3	4,5		✓
			114,3	6,3		✓			139,7	10,0		✓
			88,9	5,6		✓			114,3	8,8		✓
			88,9	6,3		✓			88,9	8,0		✓
8,8	114,3	76,1	5,0		✓	159,0	4,5	76,1	7,1		✓	
		76,1	6,3		✓			133,0	4,0		✓	
		60,3	4,5		✓			114,3	3,6		✓	
		60,3	6,3		✓			108,0	3,6		✓	
		48,3	4,0		✓			88,9	3,2		✓	
133,0	4,0	114,3	8,8		✓	168,3	4,0	168,3	4,0		✓	
		88,9	8,0		✓			4,5	168,3	4,5	✓	✓
		76,1	7,1		✓			139,7	4,0		✓	
		60,3	5,6		✓			139,7	4,5		✓	
		48,3	5,0		✓			114,3	3,6		✓	
		133,0	4,0		✓			114,3	4,5		✓	
139,7	4,0	108,0	3,6		✓	6,3	168,3	114,3	3,6		✓	
		88,9	3,2		✓			114,3	4,5		✓	
		76,1	2,9		✓			88,9	3,2	✓	✓	
		60,3	2,9		✓			76,1	2,9		✓	
		139,7	4,0		✓			60,3	2,9		✓	
		114,3	3,6		✓			114,3	4,5		✓	

Sortimentsangaben unter Vorbehalt/Assortment subject to change

## Lieferprogramm / Range of Delivery

### T-Stücke DIN 2615-1 / Tees DIN 2615-1

Abmessungen / Dimensions				Material / Material Grade		Abmessungen / Dimensions				Material / Material Grade			
d1	s1	d2	s2	St 37.0/ S235	St 35.8// P235GH	d1	s1	d2	s2	St 37.0/ S235	St 35.8// P235GH		
Außen Ø / Outside Ø	Wanddicke / Wallthickness	Außen Ø / Outside Ø	Wanddicke / Wallthickness			Außen Ø / Outside Ø	Wanddicke / Wallthickness	Außen Ø / Outside Ø	Wanddicke / Wallthickness				
mm	mm	mm	mm			mm	mm	mm	mm				
168,3	6,3	139,7	6,3		✓	219,1	8,0	139,7	6,3		✓		
		114,3	6,3		✓			114,3	6,3		✓		
	7,1	168,3	7,1		✓		88,9	5,6		✓			
		139,7	6,3		✓		60,3	4,5		✓			
		114,3	6,3		✓		8,8	219,1	8,8		✓		
		88,9	5,6		✓			168,3	6,3		✓		
		76,1	5,0		✓		12,5	219,1	12,5		✓		
		60,3	4,5		✓			168,3	11,0		✓		
	8,8	168,3	8,8		✓		139,7	10,0		✓			
		139,7	6,3		✓		114,3	8,8		✓			
	11,0	168,3	11,0		✓		88,9	8,0		✓			
			139,7	10,0			✓	60,3	5,6		✓		
			114,3	8,8			✓	267,0	6,3	267,0	6,3		✓
			88,9	8,0			✓						
76,1	7,1		✓	273,0	5,0	273,0	5,0		✓				
60,3	5,6		✓			114,3	3,6		✓				
193,7	5,6	193,7	5,6		✓	6,3	273,0	6,3		✓			
219,1	4,5	219,1	4,5		✓		219,1	6,3		✓			
		168,3	4,0		✓	168,3	4,5		✓				
		139,7	4,0		✓	159,0	4,5		✓				
	5,0	219,1	5,0		✓	139,7	4,0		✓				
		6,3	219,1	6,3		✓	114,3	3,6		✓			
	168,3		4,5		✓	108,0	3,6		✓				
	168,3		6,3		✓	8,8	273,0	8,8		✓			
	159,0		4,5		✓		219,1	8,0		✓			
	139,7		4,0		✓		168,3	7,1		✓			
	139,7		4,5		✓		139,7	6,3		✓			
	139,7		6,3		✓	114,3	6,3		✓				
	114,3		3,6		✓	10,0	273,0	10,0		✓			
	108,0		3,6		✓		219,1	8,0		✓			
	88,9		3,2		✓	168,3	7,1		✓				
76,1	2,9		✓	139,7	7,1		✓						
60,3	2,9		✓	114,3	6,3		✓						
8,0	219,1	8,0		✓	12,5	273,0	12,5		✓				
		168,3	7,1			✓	219,1	12,5		✓			
					✓	168,3	11,0		✓				

Sortimentsangaben unter Vorbehalt/Assortment subject to change

Lieferprogramm / Range of Delivery

T-Stücke DIN 2615-1 / Tees DIN 2615-1

Abmessungen / Dimensions				Material / Material Grade		Abmessungen / Dimensions				Material / Material Grade		
d1	s1	d2	s2	St 37.0/ S235	St 35.8// P235GH	d1	s1	d2	s2	St 37.0/ S235	St 35.8// P235GH	
Außen Ø / Outside Ø	Wanddicke / Wallthickness	Außen Ø / Outside Ø	Wanddicke / Wallthickness			Außen Ø / Outside Ø	Wanddicke / Wallthickness	Außen Ø / Outside Ø	Wanddicke / Wallthickness			
mm	mm	mm	mm			mm	mm	mm	mm			
273,0	12,5	139,7	10,0		✓	355,6	8,0	323,9	7,1		✓	
		114,3	8,8		✓			273,0	6,3		✓	
	14,2	273,0	14,2		✓			219,1	6,3		✓	
		219,1	12,5		✓			168,3	4,5		✓	
		168,3	11,0		✓			139,7	4,0		✓	
		139,7	10,0		✓			11,0	355,6	11,0		✓
114,3	8,8		✓	323,9	10,0		✓					
323,9	5,6	323,9	5,6		✓	273,0	8,8		✓			
		219,1	5,0		✓	219,1	8,0		✓			
		168,3	4,5		✓	168,3	7,1		✓			
	7,1	323,9	7,1		✓	139,7	6,3		✓			
			273,0	6,3		✓	219,1	6,3		✓		
			219,1	6,3		✓	168,3	4,5		✓		
			168,3	4,5		✓	139,7	4,0		✓		
			139,7	4,0		✓	114,3	3,6		✓		
			114,3	3,6		✓	8,8	355,6	12,5		✓	
	219,1	8,0		✓	323,9	12,5			✓			
	168,3	8,0		✓	273,0	12,5			✓			
	10,0	10,0	323,9	10,0		✓	219,1	12,5		✓		
			273,0	8,8		✓	168,3	11,0		✓		
			219,1	8,0		✓	17,5	355,6	17,5		✓	
			168,3	7,1		✓		323,9	16,0		✓	
			139,7	6,3		✓		273,0	14,2		✓	
			114,3	6,3		✓	219,1	12,5		✓		
		12,5	323,9	12,5		✓	406,4	6,3		✓		
				273,0	12,5		✓	323,9	5,6		✓	
				219,1	12,5		✓	8,8	406,4	8,8		✓
				168,3	11,0		✓		355,6	8,0		✓
				139,7	10,0		✓		323,9	7,1		✓
				10,0		✓	✓	273,0	6,3		✓	
	16,0	323,9	16,0		✓	219,1	6,3		✓			
273,0			14,2		✓	168,3	4,5		✓			
219,1			12,5		✓	10,0	406,4	10,0		✓		
168,3			11,0		✓		355,6	10,0		✓		
139,7			10,0		✓		323,9	10,0		✓		
				✓	✓	273,0	10,0		✓			
		✓	✓	219,1	8,0		✓					
355,6	8,0	355,6	8,0		✓	12,5	406,4	12,5		✓	✓	
					✓			355,6	11,0		✓	
					✓			355,6	12,5		✓	

Sortimentsangaben unter Vorbehalt/Assortment subject to change

Lieferprogramm / Range of Delivery

T-Stücke DIN 2615-1 / Tees DIN 2615-1

Abmessungen / Dimensions				Material / Material Grade			
d1	s1	d2	s2	St 37.0/ S235	St 35.8// P235GH		
Außen Ø / Outside Ø	Wanddicke / Wallthickness	Außen Ø / Outside Ø	Wanddicke / Wallthickness				
mm	mm	mm	mm				
406,4	12,5	323,9	10,0		✓		
		323,9	12,5		✓		
		273,0	8,8		✓		
		273,0	12,5		✓		
		219,1	8,0		✓		
		219,1	12,5		✓		
		168,3	7,1		✓		
	20,0	406,4	20,0		✓		
		355,6	17,5		✓		
		323,9	16,0		✓		
		273,0	12,5		✓		
		219,1	12,5		✓		
		419,0	10,0	419,0	10,0		✓
508,0	6,3		406,4	6,3		✓	
			323,9	6,3		✓	
			323,9	10,0		✓	
	11,0		508,0	11,0		✓	
			406,4	8,8		✓	
			355,6	8,0		✓	
			323,9	7,1		✓	
			273,0	6,3		✓	
		219,1	6,3		✓		
		406,4	12,5		✓		
610,0	12,5	508,0	11,0		✓		
		406,4	8,8		✓		

Sortimentsangaben unter Vorbehalt/Assortment subject to change

Fragen Sie uns auch nach Zwischenabmessungen, Sondermaßen und weiteren Werkstoffen /  
 Ask us also for intermediate sizes, special dimensions and other materials